



PLC-ZM5000L

- Brightness: 5000 ANSI Lumen
- Resolution: WUXGA (16:10)
- Automatic Maintenance Filter (AMF)
- 360° installation
- 5 Optional Lenses
- Mechanical Shutter
- Network Control and Monitoring

PLC-ZM5000L

TECHNICAL DETAILS

Category	Professional
Panel	3 x 0.76" Polysilicon (Inorganic)
Lamp	330w NSHA
Brightness ANSI lumens	5000
Lamp Service Life	3000h (Eco Mode), 2000h (Normal Mode)
Fan Noise	29dBA (Eco Mode)
Standard Lens	Delivery Without Lens
Throw Distance Ratio	Depending on Lens
Throw Distance	Depending on Lens
Contrast Ratio	2000:1
Resolution in pixels	1920 x 1200 (16:10)
Image size min-max (diagonal)	40" – 400"
Uniformity	90%
Bandwidth/Frequency	162MHz, Horizontal 15kHz – 120kHz, Vertical 48Hz – 100Hz
Colour Systems	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
Connections	Inputs: 1 x HDMI (v1.3) 1 x DVI-D 1 x Dsub15 1 x 5BNC 1 x 3RCA Audio In: 2 x Mini jack 1 x 2RCA Outputs: 1 x Dsub15 Audio Out: 1 x Mini Jack Control: 1 x RJ45 1 x Dsub9 1 x USB
Keystone Correction	Vertical $\pm 30^\circ$, Horizontal $\pm 30^\circ$
HDTV Signals	1080p/50, 1080p/60, 1080i/50, 1080i/60, 720p/50, 720p/60
Computer Compatibility	WUXGA, UXGA, WSXGA+, SXGA+, SXGA, WXGA, XGA, SVGA, VGA, MAC
Zoom/Focus	Depending on Lens
Power Consumption/Voltage	415w (Eco Mode), 488w (normal Mode), 0.6w (Standby Mode)
Warranty	3 Year
Dimensions (W x H x D)	489.5 x 164 x 371.1mm
Weight	9.0kg
Standard Accessories	Remote Control, Owners Manual, computer Cable (Dsub15 – Dsub15), Power Cable
Optional Accessories	POA-PN03C (Network Board)
Lenses	

* You can use the distance calculator at www.uk.sanyo.com to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 10/2010

Telephone: 01923 246363
Email: info@uk.sanyo.com
Visit: www.uk.sanyo.com

